EB-4550























The 4,500-lumen installation projector, with XGA resolution, for bright, clear images.

The EB-4550 is the XGA installation projector that offers bright, clear images, and high-end, easy-to-use features. Epson's 3LCD projector technology, and an equally high White and Colour Light Output of 4,500 lumens, ensures your important presentations are displayed with vivid, realistic colours that can be shown in a variety of ambient light levels.

The EB-4550 boasts high definition picture quality and a 5,000:1 contrast ratio. This helps showcase your important presentations and other projections in the best possible way.

Thanks to a variety of user-friendly installation features, this projector is easy to set up and use. Its x2.0 wide zoom ratio, as well as keystone correction, and arc and point correction, make it quick and easy to set up in a variety of positions without picture blurring or distortion.

With the HDMI input and Display Port, you can connect a variety of high definition devices to project your content effortlessly. In addition, the lamp and filter are easy to replace, helping keep maintenance straightforward and ensuring your projections are as bright and clear as possible.

While presenting, the side-by-side split screen function lets you present from two different sources, such as a separate laptop, for much more in-depth and impressive presentations.



KEY FEATURES

- High brightness4,500lm White and Colour Light Output
- High definition XGA resolution
- High-quality images 3LCD technology
- Rich, deep blacks 5.000:1 contrast ratio
- Split-screen
 Connect to different sources





PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology, RGB liquid crystal shutter

LCD Panel 0.63 inch with MLA (D8)

IMAGE

Colour Light Output 4,500 lumen - 3,700 lumen (economy)
White Light Output 4,500 lumen - 3,700 lumen (economy)

Resolution XGA, 1024 x 768, 4:3

Contrast Ratio 5,000 : 1

Lamp 260 W, 4,000 h durability, 5,000 h durability (economy mode)

Keystone Correction Manual vertical: \pm 30 °, Manual horizontal \pm 30 °

OPTICAL

 Projection Ratio
 1.27 - 2.59:1

 Zoom
 Manual, Factor: 1 - 2

 Image Size
 30 inches - 300 inches

 Projection Distance Wide
 0.7 m - 1.6 m (30 inch screen)

 Projection Distance Tele
 7.8 m - 15.9 m (300 inch screen)

Projection Lens F Number 1.5 - 2.14

Focal Distance 16.72 mm - 33.47 mm

Focus Manual

CONNECTIVITY

Interfaces RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), VGA in, HDMI in, Display Port,

Composite in, BNC in, S-Video in, Stereo mini jack audio out, Stereo mini jack audio in (4x),

Cinch audio in, Wireless LAN IEEE 802.11b/g/n (optional)

ADVANCED FEATURES

Security Kensington lock, Security bar, Control panel lock, Password lock

Features Direct Power on/off, Quick Corner, Six axis colour control, Split-Screen-Function

Video Colour Modes Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM

GENERAL

Energy Use 368 W, 298 W (economy), 0.39 W (standby)

OTHER

Warranty 36 months On-site service or 8,000 h, Lamp: 12 months or 1,000 h

Optional warranty extension available

LOGISTICS INFORMATION

SKU	V11H545041
EAN code	8715946530253
Dimensions Single Carton	762 x 432 x 324 mm
Carton Weight	12.9 Kg
Multiple Order Quantity	1 Units
Country of Origin	China
Pallet Size Euro	16 Units
Pallet Size Block	16 Units

EB-4550

WHAT'S IN THE BOX

- CD Manual
- Cable cover
- VGA cable
- Power cable
- Remote control incl. batteries

OPTIONAL ACCESSORIES

- Lamp ELPLP77V13H010L77
- Air Filter ELPAF45V13H134A45
- Quick Wireless Connect USB key ELPAP09 V12H005M09
- Ceiling Mount (White) ELPMB22 V12H003B22
- Ceiling Mount (Low profile) ELPMB30 V12H526040
- Ceiling Pipe (450mm) ELPFP13 V12H003P13
- Ceiling Pipe (700mm) ELPFP14 V12H003P14



For more information please contact:

Telephone: 01952 607111 (UK)+ 01 436 7742 (Republic of Ireland) E-mail: enquiries@epson.co.uk Chat: etalk.epson-europe.com Fax: 0871 222 6740 + Local call rate.

Web: www.epson.co.uk www.epson.ie

