

**A compact printer for  
flexible wide-receipt printing**



**IMAGING  
INNOVATION**



Designed to save precious retail space, the Epson LX-50 offers a smaller footprint and the flexibility of wider print options unlike traditional receipt printers. With receipts or prescription slips of up to 6" wide, you can now show more information of the transactions than before. Epson's constant innovations in retail printing solutions give you the best performing printer that suits your business requirements.

- **Wider receipt printing offers more details**  
Allow more details of transactions in a single receipt, with the flexibility of printing wider receipts of up to 6" fanfold / rollpaper.
- **Smaller footprint saves counter space**  
The compact design of only 275mm (10.83") wide allows easy installation even on counters with limited space.
- **Efficient processing time**  
High-speed processing with 64KB input data buffer reduces waiting time.

**SPECIFICATIONS**

<p><b>OPTIONS</b></p>  <p>FABRIC RIBBON CARTRIDGE (BLACK) C13S015621</p>	<p><b>PRODUCT CODE</b></p> <p>C11CB84001</p>	<p><b>PRINTER TYPE</b> PRINTING METHOD NUMBER OF PINS IN HEAD PRINT DIRECTION CONTROL CODE</p> <p>Impact dot matrix 9 pins Bi-direction with logic seeking ESC/P and IBM 2380 Plus emulation</p>
 <p>FABRIC RIBBON PACK (BLACK) C13S010086</p>	<p><b>PRINTER SPEED</b> HIGH SPEED DRAFT HIGH SPEED DRAFT CONDENSED DRAFT DRAFT CONDENSED</p> <p>10 / 12 cpi 17 / 20 cpi 10 / 12 / 15 cpi 17 / 20 cpi</p>	<p>300 / 337 cps 321 / 300 cps 225 / 270 / 225 cps 191 / 225 cps</p>
<p>ROLL PAPER HOLDER C12C811261*</p>  <p>Weight: 3.3kg 153mm (6") 240mm (9.5") 275mm (10.8")</p> <p>* paper not included</p>	<p><b>PRINT CHARACTERISTICS</b> CHARACTER SETS</p> <p>BIT MAP FONTS BAR CODE FONT</p>	<p><b>42 standard character code tables:</b> Italic table, PC437 (US Standard Europe), PC850 (Multilingual), PC860 (Portuguese), PC861 (Icelandic), PC863 (Canadian-French), PC865 (Nordic), Abicomp, BRASCII, Roman 8, ISO Latin 1, PC 858, ISO 8859-15, PC437 Greek, PC852 (East Europe), PC853 (Turkish), PC855 (Cyrillic), PC857 (Turkish), PC866 (Russian), PC869 (Greek), MAZOWLA (Poland), Code MJK (CSFR), ISO 8859-7 (Latin, Greek), ISO Latin IT (Turkish), Bulgaria (Bulgarian), Estonia (Estonia), PC774 (LST 1283:1993), ISO 8859-2, PC 866UKR (Ukraine), PC771 (Lithuania), PC437 Slovenia, PC MC, PC1250, PC1251, PCAPTEC (Arabic), PC708 (Arabic), PC720 (Arabic), PCAR 864 (Arabic)</p> <p>EPSON Draft: 10, 12, 15 cpi; EPSON Roman: 10, 12, 15 cpi, Proportional; EPSON Sans Serif: 10, 12, 15 cpi, Proportional; EPSON OCR-B: 10 cpi EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET</p>
<p>PRINTER STAND C12C847221*</p>  <p>* paper not included</p>	<p><b>PRINTABLE COLUMNS</b> PITCH</p> <p>10 cpi 12 cpi 15 cpi 17 cpi 20 cpi</p>	<p>50 cpl 60 cpl 75 cpl 85 cpl 100 cpl</p>
<p><b>LEGEND:</b> cpi : Characters per inch (Character per 25.4mm) cps : Characters per second cpl : Characters per line POH : Power On Hours</p>  <p>As an international ENERGY STAR Partner, Epson has determined that this product meets the international ENERGY STAR Programme for energy efficiency.</p>	<p><b>PAPER/MEDIA HANDLING</b> PAPER PATH PAPER SIZE CONTINUOUS PAPER ROLL PAPER PAPER FEEDING CONTINUOUS PAPER ROLL PAPER (Used with optional roll paper holder) COPIES LINE SPACING</p> <p>TRACTOR ROLL PAPER</p> <p>WIDTH x LENGTH THICKNESS WIDTH THICKNESS</p> <p>Push tractor feed Friction feed Original + 3 copies 4.23mm (1/6") or programmable in increments of 0.118mm (1/216")</p>	<p>Rear in, Top out Rear in, Top out</p> <p>101.6 ~ 152.4mm (4.0 ~ 6.0") x 101.6 ~ 558.8mm (4.0 ~ 22.0") 0.065 ~ 0.32mm (0.0025 ~ 0.0125") 101.6 ~ 127.0mm (4.0 ~ 5.0") 0.065 ~ 0.09mm (0.0025 ~ 0.0035")</p>
<p>EPSON is the registered trademark of Seiko Epson Corporation. All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. EPSON disclaims any and all rights in those marks. Scan/Print samples shown herein are simulations. Specifications are subject to change without notice.</p>	<p><b>INPUT DATA BUFFER</b></p> <p>64KB</p>	<p><b>INTERFACE</b> STANDARD</p> <p>Bi-directional parallel interface (IEEE-1284 nibble mode supported) USB 2.0 Full-Speed interface</p>
<p><b>PT EPSON INDONESIA</b> Wisma Kyoei Prince 16th Floor Jl. Jenderal Sudirman Kav.3 Jakarta Tel.(021) 5723161 Fax.(021) 5724357 Epson Call Centre (021) 5724151</p>	<p><b>EPSON SERVICE CENTRE</b> • Jakarta (021) 62301104 • Bandung (022) 4207033 • Yogyakarta (0274) 581022 • Surabaya (031) 5355035 • Medan (061) 4516173 • Pekanbaru (0761) 44270 • Pontianak (0561) 735507 • Makassar (0411) 328212</p>	<p><b>RIBBON CARTRIDGE</b> STANDARD FABRIC RIBBON CARTRIDGE (BLACK) RIBBON LIFE</p> <p>Approx. 2.5 million characters (Draft 10 cpi, 14 dots/character)</p>
<p>Information correct at time of printing.</p>	<p>Dealer's Stamp</p>  <p>Printed February 2012</p>	<p><b>HELP DESK</b> 0807 11 EPSON (3776)</p> <p><a href="http://www.epson.co.id">www.epson.co.id</a></p>  <p>Official Partner of Manchester United</p>