INK TANK SYSTEM PRINTERS

L6160/6170/6190





Experience high printing speeds and borderless printing for up to A4 size with Epson L6160/6170/6190 ink tank printers. Armed with PrecisionCore™ printheads, print speeds are improved for increased efficiency. The new tank design is integrated into the printer to allow the printer to have the smallest footprint* amongst all brands of ink tank printers that use bottled ink refills. Together with a new set of low-cost ink bottles which guarantees spill-free ink refilling and the paper-saving auto-duplex function, enjoy one of the lowest printing cost solutions. Maximise connectivity with a suite of Epson Connect features which enables printing on the go over a network.



























Each printer comes bundled with a starter kit of 1 x 127 ml bottle of black pigment ink and 3 x 70 ml bottles of colour ink

ENGINEERED FOR BUSINESS

Superior Savings with Auto-Duplex

Save up to 50% on paper costs with auto-duplex function, and enjoy even greater savings with high page yields and affordable inks.

Speed, Quality and Reliability

Epson PrecisionCore printhead offers higher print speed, quality and reliability. Pigment black ink produces water and smudge-resistant printouts.

Seamless Connectivity

Share your printer over Wi-Fi, Wi-Fi Direct, Ethernet and print on the go via a suite of Epson Connect features.





MODEL NUMBER Printer Type	Print, Scan, Copy	Print Scan Conv. with ADE	L6190 Print, Scan, Copy, Fax with ADF	Dimensions & Weight
	mint, scan, copy	Print, Scan, Copy with ADF	Print, Scan, Copy, Fax with ADF	L6160
Printing Printing Tookhoology	PrecisionCore Printhead			Weight: 5.8 kg (12.8 lb)
Printing Technology				roight die hig (nizhens)
Nozzle Configuration	400 nozzles Black, 128 nozzles per colour (C)	/an, Magenta, Yellow)		1
Print Direction	Bi-directional printing, Uni-directional printing			187 mm
Maximum Resolution	4800 x 1200 dpi (with Variable-Sized Droplet	Technology)		(7.4 ")
Minimum Ink Droplet Volume	3.3 pl			0 x x x
Print Speed ¹¹				
Draft Text - Memo, A4 (Black*1 / Colour*2)	Up to 33 ppm / 20 ppm			
ISO 24734, A4 (Black / Colour)	Simplex: Up to 15 ipm / 8.0 ipm, Duplex: 6.5 i			375 mm 347 mm
Photo Default - 10 x 15 cm / 4 x 6 " "2 #3	Approx. 69 sec per photo (Border) / 92 sec per photo (Borderless)			
Printer Language	ESC / P-R			(14.8 ")
Automatic 2-sided printing	Yes (up to A4)			L6170
Copying				Weight: 6.7 kg (14.8 lb)
Copy Speed				
ISO 29183, A4, Simplex (Black / Colour)	Simplex: Up to 11 ipm / 5.5 ipm			
Copy Quality	Normal / Best quality			231 mm
Maximum Copies from Standalone	Norman 7 Best quality 99 copies 25 - 400%, Auto Fit Function			(0.1 ")
				(9.1)
Reduction / Enlargement	600 x 1200 dpi			9 mmm
Maximum Copy Resolution	-			
Maximum Copy Size	A4, Letter			347 mm
Scanning				
Scanner Type	Flatbed colour image scanner			
Sensor Type	CIS			(14.8 ")
Optical Resolution	1200 x 2400 dpi			L6190
Maximum Scan Area	216 x 297 mm (8.5 x 11.7 ")			Weight: 6.8 kg (15.0 lb)
Scanner Bit Depth				
Colour	48-bit input, 24-bit output			^
Grayscale	16-bit input, 8-bit output			19974
Grayscale Black & White	16-bit input, 1-bit output			231 mm
	ro-bit iriput, 1-bit output			(9.1 ")
Scan Speed (Flatbed / ADF (Simplex))	40	Lancouren	140 /50	
Monochrome 200 dpi	12 sec	12 sec / 5.0 ppm	12 sec / 5.0 ppm	1
Colour 200 dpi	27 sec	27 sec / 5.0 ppm	27 sec / 5.0 ppm	
ax Function				347 mm
Type of Fax			Walk-up black-and-white and colour fax capability	375 mm (13.7 ")
Receive Memory / Page Memory	-	-	1.1 MB, Page memory, Up to 100 pages (ITU-T No.1 chart)	(14.8 ")
Error Correction Mode			ITU Group3 fax with Error Correction	
Fax Speed (Data Transfer Rate)	-	_	Up to 33.6 kbps, Approx. 3 sec/page	*1 Print speed (Pages Per Minute) is calculated when
Fax Resolution		-	Up to 200 x 200 dpi	printed on A4 plain paper in the fastest mode,
ransmission Paper Size		-		10 x 15 cm photo print speed when printed on Epso
Flatbed			Letter, A4	Premium Glossy Photo Paper. Print speed may vary depending on system configuration, print mode,
ADF		_		document complexity, software, type of paper used
	-	_	Letter, A4, 8.5 x 13 ", Legal	connectivity. Print speed does not include processin
Receiving Paper Size		_	Letter, A4, 8.5 x 13 ", Legal	time on host computer.
Speed Dial / Group Dial	<u> </u>	-	Up to 60 numbers, 30 groups	
ax Features	-	-	PC Fax (Transmission/Receive), Automatic redial, Address book,	
			Delay Send, Broadcast Fax (Mono Only)	Management
ADF Function				Name of the same o
Support Paper Thickness	-	64-95 g/m ²	64-95 g/m ²	Militaria and American
Paper Capacity	-	30 pages (75 g/m²)	30 pages (75 g/m²)	Will all the second and the second a
Paper Handling				
Paper Feed Method	Friction feed			
Number of Paper Trays	1 (Paper Cassette)			#1 #2 #3
Paper Hold Capacity				Black Text Black Text Photo 4F
Input Capacity	150 sheets, A4 Plain Paper (80 g/m²)	150 sheets, A4 Plain Paper (80 g/n	n²) 250 sheets, A4 Plain Paper (80 g/m²)	and graphics (4 x 6 ")
input capacity	20 sheets, Premium Glossy Photo Paper			*2 When printed on Epson Premium Glossy Photo Paper
Output Capacity				
Output Capacity	30 sheets, A4 Plain Paper			*3 Default mode in accordance with ISO7779 for MFPs
	20 sheets, Premium Glossy Photo Paper			*4 Otherwise 3 mm top, left, right, bottom, and except
aper Size	Legal, 8.5 x 13 *, Letter, A4, 195 x 270 mm, B5, A5, A6, 100 x 148 mm, B6, 5 x 7 *, 4 x 6 *, Envelopes #10, DL, C6			plain paper.
Naximum Paper Size	215.9 x 1200 mm (8.5 x 47.24 ")			*5 In accordance with ISO 24711/24712. Actual yields
Print Margin	0 mm top, left, right, bottom via custom settin	gs in printer driver		vary considerably for reasons including images print
nterface				print settings, temperature and humidity. Yields may
JSB	USB 2.0			be lower when printing infrequently or predominant
Network	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct	t		with one ink colour. A variable amount of ink remain
Network Protocol	TCP/IPv4, TCP/IPv6, LPD, IPP, PORT9100, W			in the cartridges after the "replace cartridge" signal.
letwork Management Protocols	SNMP, HTTP, DHCP, BOOTP, APIPA, PING, D			Part of the ink from the first cartridges is used for priming the printer. Ink is used for both printing and
Mobile and Cloud Printing				head maintenance. All inks are used for both black
pson Connect	Epson iPrint, Epson Email Print, Remote Print	Driver, Scan to Cloud		colour printing.
Other Mobile Solutions	Apple AirPrint, Google Cloud Print, Mopria Print			· · · · · · · · · · · · · · · · · · ·
Control Panel				
	2.4 * Colour I CD	2.4 " Colo - 1.0D	2.4 Colour I CD Touch Board	
.CD Screen	2.4 " Colour LCD	2.4 " Colour LCD	2.4 " Colour LCD Touch Panel	
Printer Software				Inergy ?
Operating System Compatibility	Windows XP / XP Professional x 64 Edition / \	/ista / 7 / 8 / 8.1 / 10		
	Windows Server 2003 / 2008 / 2012 / 2016			ENERGY STAR
	Only printing and scanning functions are supp	orted for Windows Server OS		
	Mac OS X 10.6.8 or later			© 2017 Epson Singapore Pte Ltd. All Rights Reserved.
Electrical Specifications				Reproduction in part or in whole, without the written
Rated Voltage	AC 100 - 240 V			permission from Epson, is strictly prohibited. EPSON an
Rated Frequency	50 - 60 Hz			EXCEED YOUR VISION are registered trademarks of Se
ower Consumption				Epson Corporation. All other products names and other company names used herein are for identification purpo
Operating	12.0 W	12.0 W	12.0 W	only and are the trademarks or registered trademarks or
	5.3 W	5.3 W	12.0 W 5.4 W	their respective owners. Epson disclaims any and all rigi
Standby		_		in those marks. Print samples shown are simulations or
Sleep	0.7 W	0.9 W	1.0 W	Specifications and product availability are subject to cha
	0.3 W	0.3 W	0.3 W	without notice and may vary between countries. Please
Power off				check with local Epson offices for more information.
Power off loise Level	38 dB (A)	38 dB (A)	38 dB (A)	
Power off loise Level	30 db (A)			
Power off loise Level C Printing / Premium Glossy	30 dB (A)		52 dB (A)	Dealer's Stamp
Power off loise Level C Printing / Premium Glossy hoto Paper Best Photo	53 dB (A)	52 dB (A)		
Power off loise Level C Printing / Premium Glossy hoto Paper Best Photo C Printing / Plain Paper Default*		•		
Power off loise Level C Printing / Premium Glossy hoto Paper Best Photo C Printing / Plain Paper Default* consumables	53 dB (A)	Code		
Power off loise Level C Printing / Premium Glossy rhoto Paper Best Photo C Printing / Plain Paper Default* consumables lack link Bottle	53 dB (A) Page Yield's Order 7,500 C13T0:	Code 3Y100		
Power off loise Level (Or Printing / Premium Glossy thoto Paper Best Photo (Or Printing / Plain Paper Default* Consumables lack Ink Bottle Cyan Ink Bottle	53 dB (A) Page Yield's Order 7,500 C13T0: C13T0:	Code 3Y100 3Y200		
Power off loise Level 'C Printing / Premium Glossy 'hoto Paper Best Photo 'C Printing / Plain Paper Default' 'Consumables Black Ink Bottle Jagenta Ink Bottle dagenta Ink Bottle	53 dB (A) Page Yield* 7,500 C13T0: C13T0: 6,000 (Composite Yield) C13T0:	Code 3Y100 3Y200 3Y300		
Power off Noise Level *C Printing / Premium Glossy *hoto Paper Best Photo *C Printing / Plain Paper Default* *Consumables slack Ink Bottle *Joyan Ink Bottle *Jagenta Ink Bottle *Jagenta Ink Bottle	53 dB (A) Page Yield* 7,500 C13T0: 6,000 (Composite Yield) C13T0: C13T0:	Code 3Y100 3Y200 3Y300 3Y400		Information correct at time of printing
Power off oise Level C Printing / Premium Giossy hoto Paper Best Photo C Printing / Plain Paper Default* onsumables lack Ink Bottle yan Ink Bottle lagenta Ink Bottle	53 dB (A) Page Yield* 7,500 C13T0: C13T0: 6,000 (Composite Yield) C13T0:	Code 3Y100 3Y200 3Y300 3Y400		Information correct at time of printing Printed August 2017

For latest specifications, simply visit www.epson.com.sg/inktankprinter or call 800 120 5564.