




9-PIN DOT MATRIX PRINTER

FX-2175



**A LOW MAINTENANCE
AND HIGH
PERFORMANCE
WORKHORSE**

**9-PIN DOT MATRIX PRINTER
FX-2175**



Weight = Approx. 9.1kg

INDIA

Epson India Pvt Ltd
Tel: (91) 080-3051-5000
Fax: (91) 080-3051-5005
www.epson.co.in

INDONESIA

PT Epson Indonesia
Tel: (62) 021-572-3161
Fax: (62) 021-572-4357
www.epson.co.id

MALAYSIA

Epson Trading (M) Sdn Bhd
Tel: (60) 03-5628-8288
Fax: (60) 03-5628-8388
www.epson.com.my

PHILIPPINES

Epson Philippines Corporation
Tel: (63) 02-813-6567
Fax: (63) 02-811-1163
www.epson.com.ph

SINGAPORE

Epson Singapore Pte Ltd
Tel: (65) 6586-5500
Fax: (65) 6271-7066
www.epson.com.sg

THAILAND / INDOCHINA

Epson (Thailand) Co., Ltd
Tel: (66) 02-670-0680
Fax: (66) 02-670-0688
www.epson.co.th

Specifications

Printer Type	Printing Method	Impact Dot Matrix
	Number of Pins in Head	9 Pins
	Colour	Black
	Print Direction	Bi-Direction with Logic Seeking
	Control Code	ESC/P®, IBM® PPDS Emulation
Print Speed	High Speed Draft	10 cpi 476 cps 12 cpi 539 cps
	Draft	10 cpi 347 cps 12 cpi 416 cps
	NLQ	10 cpi 87 cps 12 cpi 105 cps
Print Characteristics	13 International Character Sets	
Character Table	For Standard Version: Italic Table, PC437(US, Standard Europe), PC850(Multilingual), PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), PC861(Icelandic), BRASCL1, Abicomp, Roman 8, ISO Latin 1, PC858, ISO 8859-15	
	For NLSP Version: Italic table, PC437(US, Standard Europe), PC850(Multilingual), PC437 Greek, PC853(Turkish), PC855(Cyrillic), PC852(East Europe), PC857(Turkish), PC866(Russian), PC869(Greek), MAZOWIA(Poland), Code MJK(CSFR), ISO 8859-7(Latin/Greek), ISO Latin 1T(Turkish), Bulgaria(Bulgarian), PC774(LST 1283:1993), Eastonia(Estonia), ISO 8859-2, PC866 LAT. (Latvian), PC866 UKR(Ukraine), PC860(Portuguese), PC861(Icelandic), PC865(Nordic), PC APTTEC(Arabic), PC708(Arabic), PC720(Arabic), PCAR864(Arabic) PC863(Canadian-French), BRASCL1, Abicomp, Roman 8, ISO Latin 1, PC858, ISO 8859-15, PC771(Lithuania), PC437 Slovenia, PCMC, PC1250, PC 1251	
	Bit Map Font	EPSON Draft 10 cpi, 12 cpi, 15 cpi EPSON Roman 10 cpi, 12 cpi, 15 cpi, Proportional EPSON Sans Serif 10 cpi, 12 cpi, 15 cpi, Proportional
	Bar Code	EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, CODE 128, POSTNET
Printable Columns	Pitch	(Characters Per Line)
	10 cpi	136
	12 cpi	163
	15 cpi	204
	17 cpi	233
	20 cpi	272
Paper Handling	Tractor (Front or Rear In, Top Out)	
Paper Path	Tractor (Front or Rear In, Top Out)	
Paper / Media	Cut Sheet (Single Sheet)	Width 100 – 420 mm (3.9 – 16.5 Inch) Length 100 – 364 mm (3.9 – 14.3 Inch) Thickness 0.065 – 0.14 mm (0.0025 – 0.0055 Inch)
	(Multi part)	Width 100 – 420 mm (3.9 – 16.5 Inch) Length 100 – 364 mm (3.9 – 14.3 Inch) Thickness 0.12 – 0.39 mm (0.0047 – 0.015 Inch)
	Card	Width 100 – 148 mm (3.9 – 5.8 Inch) Length 148 mm (5.8 Inch) Thickness 0.22 mm (0.0087 Inch)
	Envelope (No. 6)	Width 165 mm (6.5 Inch) Length 92 mm (3.6 Inch) Thickness 0.16 – 0.52 mm (0.0063 – 0.0205 Inch)
	(No. 10)	Width 241 mm (9.5 Inch) Length 105 mm (4.1 Inch) Thickness 0.16 – 0.52 mm (0.0063 – 0.0205 Inch)
	Continuous Paper (Single Sheet/ Multi Part)	Width 101.6 – 406.4 mm (4 – 16 Inch) Length 101.6 – 558.8 mm (4 – 22 Inch) Thickness 0.065 – 0.39 mm (0.0025 – 0.015 Inch)
Copies	1 Original + 4 Copies Always	
Line Spacing	4.23 mm (1/6 Inch) or programmable in increments of 0.059 mm (1/432 Inch)	
Input Data Buffer	128 kbytes	
Interface	Bi-Directional Parallel Interface (IEEE-1284 Nibble Mode Supported, USB (Ver.1.1) I/F, Type B I/F level 2 (Option))	
Ribbon Cartridge	Colour	Black
	Type	Fabric
	Ribbon Life	12 Million Characters (Draft 10 cpi, 14 Dots/Character)
Acoustic Noise	Level 55 dB(A) (ISO 7779 Pattern)	
Reliability	Mean Print Volume Between Failure (MVBF):	25 Million Lines (Except Print Head)
	MTBF:	12,000 POH (25% Duty Cycle)
	Print Head Life:	200 Million Strokes/Wire (Draft 10 cpi, 14 Dots/Character)
Control Panel	6 Switches and 10 LEDs	
Environmental Conditions (Operating)	Temperature 5 – 35°C	Humidity 10 – 80% RH
Electrical Specifications	Rated Voltage	AC 220–240V
	Rated Frequency	50–60Hz
	Power Consumption	Approx. 55W (ISO/IEC 10561 Letter Pattern) Approx. 4.5W in Sleep Mode Energy Star Compliant
Dimensions	Width 589 mm	Depth 350 mm
	Height 1675 mm	Weight Approx. 9.1 kg
Printer Driver/Utility	OS	Microsoft® Windows® 95/98/2000/Me/XP and Microsoft® Windows® NT® Operating System Version 4.0
	Utility	EPSON Status Monitor 3 (Microsoft® Windows® 95/98/2000/Me/XP and Microsoft® Windows® NT® Operating System Version 4.0 Environment only)
Options	Ribbon Cartridge (Black)	C13S015330
	High Capacity Cut Sheet Feeder (Bin 1)	C12C806402
	Single Bin Cut Sheet Feeder	C12C806392
	Pull Tractor Unit	C12C800212
	Roll Paper Holder	C12C811141
	Front Sheet Guide	C12C814011
	Front Paper Guide	C12C814032
	Serial I/F Card	C12C823061
	32KB Intelligent Serial I/F Card	C12C823081
	IEEE-1284 Parallel I/F Card	C12C823453
	EpsonNet 10/100 Base Tx Int. Print Server 5	C12C824343

Dealer's Stamp

EPSON
EXCEED YOUR VISION